



Description:

For an easier filter insert removal in deeper installations.

Accessory for the 3P Volume Filter, 3P Patronen Filter, 3P Kompakt Filter and 3P Sinus Filter

Installation: The user has to drill a hole through the lid of the integrated filter and has to mount the removal handle. The cartridge is fastened inside the lid of the filter. Therefore it can be taken out easily for maintenance.

With the 3P Volumenfilter the hole has to be drilled central in the handle bar of the filter insert.

Technical Data:

Thread rod M8: stainless steel
plus 2 screw nuts of stainless steel and grommets
Length: 50 cm
Knob: Plastic
Weight: 0,2 kg

Packing unit

3P Removal Handle:

Covering box 790 x 575 x 700 mm: 150 pieces
Pallet: 900 pieces

3P Removal Handle

Art.-Nr. 1000550



Description:

Clamp of plastic with a diameter DN 100 for the safe assembly of pipes to pipe connections inside the rainwater tank

Consisting of: Clamp of plastic DN 100, one sleeve for sealing EPDM as well as 2 screws with screw nuts and grommets

Technical Data:

Width: 9 cm
InnerØ DN 100
Material clamp: Polyethylene
Material sealing: EPDM
Material nuts M8, screw nuts and grommets: stainless steel
Weight: 0,3 kg

Special design available:

Art.-Nr. 4000740

Rapid Connection one-piece

Art.-Nr. 4000760

Rapid Connection threepart

Packing unit 3P Rapid Connection:

Covering box 790 x 575 x 700 mm: 168 pieces
Pallet: 1008 pieces

3P Rapid Connection

Art.-Nr. 4000750



How it works:

The sleeve for sealing is pushed over the pipe, then the connection. The nuts are released.

After that the pipe connection is set against the pipe, the sleeve sealing is pushed half over both pipes as well as the connection.

Then you have to tighten the nuts until you cannot turn the connection any more.

